

OESA/OS switch disconnecter fuse, DIN-types

DIN type

32 - 800A SDF supplied with shaft and IP65 handle

Mechanism at the end of the switch fuse



Rated current In [A]	Poles	Recommend Fuse size	Description	Ordering code
32	3	000 / 00	OESA00-32	1SCA022058R7710
63			OESA 00-63	1SCA022057R6850
100		00	OESA00 100	1SCA022025R7830
125			OESA 00125	OESA00125 ■
160		0	OESA00-160	1SCA022077R8130 ■
200			OS200D03P	1SYN022709R9500 ■
250		0-1	OS250D03P	1SYN022719R0090
315		0-2	OS315D03P	1SYN953046P3001
400			OS400D03P	1SYN022719R0250
630		3	OS630D03P	1SYN022825R2830 ■
800	OS800D03P		1SYN022825R4880	
32	TPN	000 / 00	OESA0032N	OESA0032N ■
63			OESA0063N	OESA0063N ■
100		00	OESA00100N	OESA00100N
125			OESA00125N	OESA00125N ■
160		0	OESA00160N	OESA00160N
200			OS200D03N3P	1SYN022749R8710 ■
250		0-1	OS250D03N3P	1SYN022749R9430
315		0-2	OS315D03N3P	1SYN953047P3001
400			OS400D03N3P	1SYN022753R9320 ■
630		3	OS630D03N3P	1SYN100858R1001 ■
800	OS800D03N3P		1SYN100859R1001	
32	4	000 / 00	OESA 00-32A4	1SCA022067R7610
63			OESA 00-63A4	1SCA022057R7740
100		00	OESA00100A4	1SCA022043R6760
125			OESA00125A4	OESA00125A4
160		0	OESA 00-160A4	1SCA022080R7840
200			OS200D04N2P	1SYN022709R9680
250		0-1	OS250D04N2P	1SYN022719R2380
315		0-2	OS315D04N2P	1SYN953048P3001
400			OS400D04N2P	1SYN022719R2460
630		3	OS630D04N2P	1SYN022825R4290
800	OS800D04N2P		1SYN022825R5180	

Notes:

4th pole of all SFU's are 100% rated and are in the switched neutral (SN) version.

Contact our nearest sales office

- For 1250A Switch disconnecter fuse requirement
- For mechanism inbetween poles configuration
- For Motorized Switch disconnecter fuse requirement
- For 2 pole Switch disconnecter fuse
- For 4th pole has fuse protection
- For Switch disconnecter fuse with direct mounting handle


OESA/OS switch disconnecter fuse, BS-types

BS

32 - 800A SDF supplied with shaft and IP65 handle

Mechanism at the end of the switch fuse

1



Rated current In [A]	Poles	Recommend Fuse size	Description	Ordering code	
32	3	A2	OESA32G1	1SCA022057R1540	
63		A3	OESA63G1	1SCA022057R0310 ■	
100		A4	OESA100G1	1SCA022042R0920 ■	
125			OESA125G1	OESA125G1	
160		B2	OESA160B3	1SCA022076R9570	
200		B1-B2	OS200B03P	1SYN022709R9330	
250		B1-B3	OS250B03P	1SYN022750R6660	
315		B1-B4	OS315B03P	1SYN022719R0680	
400			OS400B03P	1SYN022719R0840	
630		C1-C2	OS630B03P	1SYN022825R5850	
800		C1-C3	OS800B03P	1SYN022825R7550	
32		TPN	A2	OESA32G1N	OESA32G1N ■
63			A3	OESA63G1N	OESA63G1N ■
100	A4		OESA100G1N	OESA100G1N ■	
125			OESA125G1N	OESA125G1N ■	
160	B2		OESA160B3N	OESA160B3N	
200	B1-B2		OS200B03N3P	1SYN022750R0620 ■	
250	B1-B3		OS250B03N3P	1SYN022750R8010 ■	
315	B1-B4		OS315B03N3P	1SYN022753R8940	
400			OS400B03N3P	1SYN022753R9160	
630	C1-C2		OS630B03N3P	1SYN100860R1001	
800	C1-C3		OS800B03N3P	1SYN100861R1001	
32	4		A2	OESA32G4	1SCA022059R9040
63			A3	OESA63G4	1SCA022057R1110
100		A4	OESA100G4	1SCA022043R7570	
125			OESA125G4	OESA125G4	
160		B2	OESA160B4	1SCA022080R3690	
200		B1-B2	OS200B04N2P	1SYN022709R9410	
250		B1-B3	OS250B04N2P	1SYN022750R7800	
315		B1-B4	OS315B04N2P	1SYN022719R2710	
400			OS400B04N2P	1SYN022719R2890	
630		C1-C2	OS630B04N2P	1SYN022825R6230	
800		C1-C3	OS800B04N2P	1SYN022825R8010	

Note:

4th pole of all SFU's are 100% rated and are in the switched neutral (SN) version.

Contact our nearest sales office

- For 1250A Switch disconnecter fuse requirement
- For mechanism inbetween poles configuration
- For Motorized Switch disconnecter fuse requirement
- For 2 pole Switch disconnecter fuse
- For 4th pole has fuse protection

■ Stock items