

Leading the way in new innovative circuit protection



With effect from 15th November, 2025



Powering Business Worldwide

About EAT•N

Eaton is an intelligent power management company dedicated to protecting the environment and improving the quality of life for people everywhere. We provide sustainable solutions that help our customers manage electrical and mechanical power—more safely, efficiently, and reliably. By capitalizing on the global growth trends of electrification and digitalization, we are accelerating the planet's transition to renewable energy, solving the world's most urgent power management challenges, and building a more sustainable society for today and generations to come.

Eaton was founded in 1911 and has continuously evolved to meet the changing needs of industries worldwide. In 2024, our revenues reached nearly \$25 billion, and we serve customers in more than 160 countries. Eaton has approximately 92,000 employees globally. The company first established a presence in the Asia Pacific region in the 1970s. Since then, our presence has grown significantly, with a fast-expanding network of sales and marketing offices, manufacturing plants, service centers, and research facilities in the region.

Today, we have nearly 17,000 employees, 6 R&D centers, and operate 34 manufacturing facilities across countries and regions including China, India, Japan, South Korea, Singapore, Indonesia, Thailand, the Philippines, and Australia for all of Eaton's distinct business segments.

Operating in
160+
countries

92,000+
employees

100+
years of
experience

\$24.9
BILLION IN
SALES 2024

18,000+
patents

A legacy of innovation

We make stronger together work.*

US-focused power
distribution
and control business

Power quality and
datacenter market

Global geographic
expansion

Built scale

Extended
capabilities

Scaling
Precision



POWERWARE

MOELLER



INNOVATIVE SWITCHGEAR

Switchgear, Motor Protection



المنتجات الكهربائية
التي تعمل على تحسين
كفاءة الطاقة



1979 1994

2004

2008

2013

2019 - 2021

2022-2025



We have built our capabilities and expanded through key acquisitions and partnerships...

© 2025 Eaton. All rights reserved..

Contact Eaton today to learn how the Eaton
can Transform your power Infrastructure

Visit [Eaton.com/in](https://eaton.com/in) for more information

Eaton Power Quality Pvt. Ltd. 2, EVR Street, Sedarpet Industrial Estate Pondicherry - 605111 | Tel: +91 413 2672000

Specifications subject to change without notice. ©2025 Eaton Corporation. All rights reserved.

Eaton's Product Range

Low Voltage Distribution Products

Air Circuit Breakers	PSL / IZM
Molded Case Circuit Breakers	PDC / NZM / BZMx
Disconnectors	P / PN
Mining Duty Breakers	
ATS	



Contactors

Mini Contactors & Control Relays	DILEM / DILEEM / DILER
Control Relays & Power Contactors	DILM / DILA / XTC
Vacuum Contactors	DILM / DILH / V201
4 Pole Contactors	DILMP
Capacitor Duty Contactors	DILK
DC Mill Duty Contactors	
DC Power Contactors	
Definite Purpose Contactors	



Overload Relays

Thermal Magnetic Overload Relay	ZB/ZE/ZEB
Motor Management Relay	Motor Insight, C440
Thermistor Based Overload Relays	EMT6



Motor Protection Circuit Breakers (MPCB)

MPCB with Push Button Control	PKZM01
MPCB with Rotary Handle Control	PKZM0
MPCB with Electronic Release	PKE



Low Voltage Control Products

Pilot Devices (22.5mm & 16mm)	RMQTitan (M22) / A22
Pilot Devices (30.5mm)	E30/E34/10250T
Foot & Palm Switch	FAK
Signal Towers	SL
Pressure Switches	MCS
Position Switches / Safety Switches ...	LS
Sensors	Inductive / Capacitive / Optical
Limit Switches	Precision / Mini / Metal / Metal-IP67 / Hazardous Applications



w.e.f from 15th November, 2025

Eaton's Product Range

Cam Switches & Switch - Disconnectors

Cam Switches upto 132KW.....	T
Switch-Disconnector upto 110KW/315A	P
ATEX Rated Enclosures	T/P



Electronic Relays

Safety Relay	ESR5
Safety Control Relays	Easy Safety
Timing Relays	ETR2 / ETR4
Measuring & Monitoring Relays	EMR



Automation Products

Relays	Easy500/700/800
PLC's	XC / EC4
HMI/ HMI-PLC's	XVC
Smartwire Darwin Communication System	



Motor Starters

DOL / RDOL Starter upto 32A with PKZM0	
DOL / RDOL Starter upto 32A with PKE	
Soft Starters upto 900KW.....	S8014/S8114
Variable Speed Starter	DE1
Variable Speed Drive	DG1/DF1/DV1



Enclosures

IP65, Outdoor rated Polycarbonate Opaque/Transparent ...	CI /CI-K
MCB Individual Enclosure	AE...
MCCB / Switch Disconnector	MCCB...
Fuse Enclosure	RS..



Solar Products

Air Circuit Breakers upto 4000A, 690V/800V/1140V/1500V AC
Moulded Case Circuit Breakers upto 1600A, 800V/1000V AC
Miniature Circuit Breakers upto 63A, 500V DC/1000V DC
Disconnectors upto 60A, 1000V DC rated
Disconnectors, 160A - 1400A, 1500V DC rated
Fuse & Fuse Base, 1000V DC
Inverters upto 1MW
DC Combiner Boxes
AC Switchgear



w.e.f from 15th November, 2025

Contents

Low Voltage Fuse Links & Fuse Holders

HRC Fuse Fittings & Bases	5
Low Voltage BS88 Type of Fuse Links	5 - 8
Low Voltage NH Type of Fuse Links	9

Highspeed Voltage Fuse Links

BS88 Semi-Conductor Protection, Highspeed Fuses	10 - 11
Accessories for BS88 Highspeed Fuses	12

High Voltage Fuse Links

BS Type HV Fuses for use in Air	13 - 14
HV Fuses for use in Oil	15
HV Fuses for use in PT/VT & Auxillary Transformer	15
HV Fuses for use in for HV Motor Circuits	16

Fuse Range

Low Voltage BS88 Type of Fuse Links Range	17 - 18
Highspeed Voltage Fuse Links Range	19 - 20
Medium Voltage Fuse Links	21
HV Fuses for use in Motor Circuits	22

Cross Reference Chart

Cross Reference Chart	23
-----------------------	----

Fuse Base for LV NH Type of Fuse

IS / BS Size Reference	Description	No. of Poles	Suitable for Fuse Type	Rating (Amps)	Cat. No. / Type	Rated Voltage (Volts)	MRP (₹)	Pack Qty.	MOQ	Delivery Class
00 / C00	Fuse Base	Single	DIN Size 00/000	160	SD00-D	690	450	3	3	O
00 / C00	Cover	Single	For holder SD00-D	160	SD00-SK*	690	-	-	3	O
00 / C00	Phase Barrier	Single	For holder SD00-D	160	SD00-PB**	690	-	-	6	O

Available on Request
 *Kit includes Cover (3), Shroud (6)
 **Barrier (2)

Fuse Fittings for LV BS Type of Fuses

IS / BS Size Reference	Tag Type	Connection Type	Suitable for Fuse Type	Rating (Amps)	Cat. No. / Type	Rated Voltage (Volts)	MRP (₹)	Carton Qty.	MOQ	Delivery Class
F1	Clip on	Front	F06/NSD	20	FA20	500	190	10	10	N
		Front	F06/NSD	32	FA32	500	200	10	10	N
		Back	F06/NSD	32	FB32	500	275	10	10	N
		Busbar	F06/NSD	32	FD32	500	270	10	10	N
A2	Offset Bolted	Front	H07/F07/AAO	32	HA32	500	335	5	5	N
		Busbar	H07/F07/AAO	32	HD32	500	410	5	5	N
A3	Offset Bolted	Front	T07/BAO/KO7	63	KA63	500	435	5	5	N
		Busbar	T07/BAO/KO7	63	KD63	500	520	5	5	N
A4	Offset Bolted	Front	L14/KL14/M14	100/125	LA125	500	1235	1	1	N
		Busbar	L14/KL14/M14	100/125	LD125	500	1620	1	1	N
F1	Clip on	Front (#)	F06/NSD	32	32NNSF	550	270	10	10	N
		Front	ESD	63	63ENSF	415	2020	5	5	O

Safe lock Range - Screw as wells as DIN Rail fixing (#)

(#) Available on request Busbar / Stud Mounting
 In White / Grey Body

Low Voltage BS88 - Clip on Type of Fuses

240 / 550 Vac	BS Size	Tag Type	Rated Voltage (Volts)	Breaking Capacity (kA)	Rating (Amps)	Cat. No./ Type	MRP (₹)	Carton Qty.	MOQ	
	E1	SMALL CLIP	240	33	2	SSD2	80	20	20	N
		ON	240	33	4	SSD4	80	20	20	N
			40	33	6	SSD6	80	20	20	N
			240	33	10	SSD10	80	20	20	N
			240	33	16	SSD16	90	20	20	N
			240	33	20	SSD20	90	20	20	N
			240	33	25	SSD25	95	20	20	O
	F1	CLIP ON	550	80	2	NSD2	70	20	20	N
		TAG	550	80	4	NSD4	70	20	20	N
			550	80	6	NSD6	70	20	20	N
			550	80	10	NSD10	70	20	20	N
			550	80	16	NSD16	80	20	20	N
			550	80	20	NSD20	80	20	20	N
			550	80	25	NSD25	85	20	20	N
	F2	LONG CLIP	550	80	2	ESD2	120	20	20	O
		ON	550	80	4	ESD4	120	20	20	O
			550	80	6	ESD6	120	20	20	O
			550	80	10	ESD10	120	20	20	O
			550	80	16	ESD16	120	20	20	O
			550	80	20	ESD20	120	20	20	O
			550	80	25	ESD25	125	20	20	O
			550	80	32	ESD32	125	20	20	O
			550	80	40	ESD40	160	20	20	O
			550	80	50	ESD50	160	20	20	N
			550	80	63	ESD63	160	20	20	N

N - Normal; O - On Order

w.e.f from 15th November, 2025

Low Voltage BS88 Type of fuses

Bolted Type, 660/690 Volts range, Breaking Capacity - 80kA

660 / 690 Vac	BS Size	Tag Type	Rated Voltage (Volts)	Rating (Amps)	Cat. No./ Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class	
	A2	OFF SET TAG	660 / 690	2	2HO7-660	130	20	20	N	TIA
		CLOSED SLOT	660 / 690	4	4HO7-660	130	20	20	N	
			660 / 690	6	6HO7-660	130	20	20	N	
			660 / 690	10	10HO7-660	150	20	20	N	
			660 / 690	16	16HO7-660	150	20	20	N	
			660 / 690	20	20HO7-660	150	20	20	N	
			660 / 690	25	25HO7-660	150	20	20	N	
			660 / 690	32	32HO7-660	150	20	20	N	
	A3	OFF SET TAG	660 / 690	35	35KO7-660	210	20	20	N	TIS
		CLOSED SLOT	660 / 690	40	40KO7-660	210	20	20	N	
			660 / 690	50	50KO7-660	225	20	20	N	
			660 / 690	63	63KO7-660	225	20	20	N	
	A4	OFF SET TAG	660 / 690	80	80L14-660	365	10	10	N	TCP
		CLOSED SLOT	660 / 690	100	100L14-660	365	10	10	N	
	-	OFF SET TAG	660 / 690	125	125M14-660	745	5	5	N	TFP
		CLOSED SLOT	660 / 690	160	160M14-660	800	5	5	N	
			660 / 690	200	200M14-660	825	5	5	N	

N - Normal; O - On Order

Bolted Type, 660/690 Volts range, Breaking Capacity - 80kA

660 / 690 Vac	BS Size	Tag Type	Rated Voltage (Volts)	Rating (Amps)	Cat. No./ Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class	
	B1	CENTRE TAG	660 / 690	80	80LO9-660	415	10	10	O	TC
		SINGLE SLOT	660 / 690	100	100LO9-660	420	10	10	N	
	B2	CENTRE TAG	660 / 690	125	125MO9-660	810	5	5	N	TF
		SINGLE SLOT	660 / 690	160	160MO9-660	825	5	5	N	
			660 / 690	200	200MO9-660	905	5	5	N	
	B3	CENTRE TAG	660 / 690	250	250NO9-660	1530	1	1	N	TKF
		SINGLE SLOT	660 / 690	315	315NO9-660	1550	1	1	N	
	C1	CENTRE TAG	660 / 690	355	355P11-660	1750	1	1	O	TMF
		DOUBLE SLOT	660 / 690	400	400P11-660	1945	1	1	O	
	C2	CENTRE TAG	660 / 690	450	450R11-660	2270	1	1	O	TM
		DOUBLE SLOT	660 / 690	500	500R11-660	2270	1	1	O	
			660 / 690	560	560R11-660	2560	1	1	O	TTM
			660 / 690	630	630R11-660	2720	1	1	O	

N - Normal; O - On Order

w.e.f from 15th November, 2025

Low Voltage BS88 Type of fuses

Bolted Type, 550 Volts range, Breaking Capacity - 80kA

550 Vac	BS Size	Tag Type	Rated Voltage (Volts)	Rating (Amps)	Cat. No./ Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class	
	-	OFFSET TAG	550	2	NITD2	105	20	20	N	NIT
		OPEN SLOT	550	4	NITD4	105	20	20	N	
			550	6	NITD6	105	20	20	N	
			550	10	NITD10	105	20	20	N	
			550	16	NITD16	105	20	20	N	
			550	20	NITD20	105	20	20	N	
			550	25	NITD25	115	20	20	O	
			550	32	NITD32	115	20	20	O	TSA
	A2	OFFSET TAG	550	2	AAO2	90	20	20	N	
		CLOSED SLOT	550	4	AAO4	90	20	20	O	
			550	6	AAO6	90	20	20	N	
			550	10	AAO10	90	20	20	N	
			550	16	AAO16	90	20	20	N	
			550	20	AAO20	105	20	20	N	
			550	25	AAO25	105	20	20	N	
			550	32	AAO32	105	20	20	N	
	A3	OFFSET TAG	550	35	BAO35	165	20	20	N	TSS
		CLOSED SLOT	550	40	BAO40	165	20	20	N	
		(@)	550	50	BAO50	175	20	20	N	
			550	63	BAO63	190	20	20	N	
	-	OFFSET TAG	550	80	OSD80	415	20	20	N	TSDS
		CLOSED SLOT	550	100	OSD100	455	20	20	N	

Note: (@) - KO7 - Open Slot, BAO - Closed Slot
N - Normal; O - On Order

Bolted Type, 550 Volts range, Breaking Capacity - 80kA

550 Vac	BS Size	Tag Type	Rated Voltage (Volts)	Rating (Amps)	Cat. No./ Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class	
	C2	CENTRE TAG	550	450	FF450	2750	1	1	O	TST
		DOUBLE SLOT	550	500	FF500	2890	1	1	O	
			550	560	FF560	3180	1	1	O	
			550	630	FF630	3465	1	1	O	
	C3	CENTRE TAG	550	710	GF710	3690	1	1	O	TLM
		DOUBLE SLOT	550	800	GF800	3690	1	1	O	
	-	CENTRE TAG	550	710	GG710	#	1	3	O	TLT
		DOUBLE SLOT	550	800	GG800	#	1	3	O	
			550	1000	GG1000	#	1	3	O	
			550	1250	GG1250	#	1	3	O	

- Price Available on request
N - Normal; O - On Order

w.e.f from 15th November, 2025

Bolted Type, 415 Volts range, Breaking Capacity - 80kA

415 Vac	BS Size	Tag Type	Rated Voltage (Volts)	Rating (Amps)	Cat. No./ Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class	
	-	OFFSET TAG	550	2	EITD2	120	20	20	N	EIT
		OPEN SLOT	550	4	EITD4	120	20	20	N	
			550	6	EITD6	120	20	20	N	
			550	10	EITD10	120	20	20	N	
			550	16	EITD16	130	20	20	N	
			550	20	EITD20	130	20	20	N	
			550	25	EITD25	130	20	20	N	
			550	32	EITD32	150	20	20	N	
			415	40	EITD40	150	20	20	N	
			415	50	EITD50	160	20	20	N	
			415	63	EITD63	160	20	20	N	
	A4	OFFSET TAG	415	32	CEO32	285	10	10	O	TSD
		CLOSED SLOT	415	40	CEO40	285	10	10	O	
			415	50	CEO50	320	10	10	O	
			415	63	CEO63	320	10	10	O	
			415	80	CEO80	395	10	10	N	
			415	100	CEO100	455	10	10	N	
	-	OFFSET TAG	415	125	DEO125	415	5	5	N	TSFP
		CLOSED SLOT	415	160	DEO160	460	5	5	N	
			415	200	DEO200	510	5	5	O	
	B1	CENTRE TAG	415	80	CD80	420	10	10	O	TSDC
		SINGLE SLOT	415	100	CD100	570	10	10	N	
	B2	CENTRE TAG	415	125	DD125	495	5	5	N	TSF
		SINGLE SLOT	415	160	DD160	520	5	5	N	
			415	200	DD200	550	5	5	N	
			415	250	ED250	1085	1	1	N	
	B3 / B4	CENTRE TAG	415	250	ED250	1085	1	1	N	TSF/TSK
		SINGLE SLOT								
	B3/B4	CENTRE TAG	415	315	ED315	1195	1	1	N	TSK
		SINGLE SLOT								
	B4	CENTRE TAG	415	355	ED355	1240	1	1	O	TSK/TSM
		SINGLE SLOT	415	400	ED400	1280	1	1	N	

N - Normal; O - On Order

Bolted Type, 415 Volts range, Breaking Capacity - 80kA

415 Vac	BS Size	Tag Type	Rated Voltage (Volts)	Rating (Amps)	Cat. No./ Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class	
	-	CENTRE TAG	415	355	355SN11(S)	1540	1	1	O	TSMS
		SINGLE SLOT	415	400	400SN11(S)	1540	1	1	N	
	-	CENTRE TAG	415	450	450SP11(S)	1880	1	1	O	TSTS
		SINGLE SLOT	415	500	500SP11(S)	2170	1	1	O	
	-	CENTRE TAG	415	560	560SR11(S)	2890	1	1	O	TSLS
		SINGLE SLOT	415	630	630SR11(S)	3320	1	1	N	
			415	710	710SR11(S)	-	1	1	O	
			415	800	800SR11(S)	3690	1	1	N	
	C1	CENTRE TAG	415	355	EF355	2535	1	1	O	TSM
		DOUBLE SLOT	415	400	EF400	2535	1	1	O	
	-	CENTRE TAG	415	710	710SR11	4605	1	1	O	TSL
		DOUBLE SLOT	415	800	800SR11	4605	1	1	N	

N - Normal; O - On Order

w.e.f from 15th November, 2025

Low Voltage DIN Type, NH Dual Indicator Fuse Links

Rated Voltage 500 Volts AC, Breaking Capacity - 120 kA

500 Vac	Size	Rated Current (A)	Class gL-gG with Dual Indication & Metal Grips	MRP (₹)	Carton Qty.	MOQ	Delivery Class
	000	2	2NHG000B	445	3	3	N
		4	4NHG000B	445	3	3	N
		6	6NHG000B	445	3	3	N
		10	10NHG000B	445	3	3	N
		16	16NHG000B	445	3	3	N
		20	20NHG000B	465	3	3	N
		25	25NHG000B	465	3	3	N
		32	32NHG000B	465	3	3	N
		35	35NHG000B	465	3	3	O
		40	40NHG000B	510	3	3	N
		50	50NHG000B	510	3	3	N
		63	63NHG000B	510	3	3	N
		80	80NHG000B	525	3	3	N
		100	100NHG000B	540	3	3	N
	00	63	63NHG00B	535	3	3	N
		80	80NHG00B	580	3	3	N
		100	100NHG00B	580	3	3	N
		125	125NHG00B	580	3	3	N
	0®	160	160NHG00B	605	3	3	O
		50	50NHG0B	715	3	3	O
		63	63NHG0B	715	3	3	O
		80	80NHG0B	785	3	3	O
	0s	100	100NHG0B	785	3	3	O
		125	125NHG0B	785	3	3	O
		160	160NHG0B	795	3	3	O
		200	200NHG0SB	830	3	3	O
	01®	100	100NHG01B	825	3	3	O
		125	125NHG01B	825	3	3	O
		160	160NHG01B	850	3	3	O
		200	200NHG1B	890	3	3	N
	1	224	224NHG1B	890	3	3	O
		250	250NHG1B	940	3	3	N
		315#	315NHG1B#	1160	3	3	O
		355	355NHG1B	1190	3	3	O
	02	35	35NHG02B	870	3	3	O
		40	40NHG02B	870	3	3	O
		50	50NHG02B	870	3	3	O
		63	63NHG02B	870	3	3	O
		80	80NHG02B	870	3	3	O
		100	100NHG02B	960	3	3	O
		125	125NHG02B	985	3	3	O
		160	160NHG02B	1000	3	3	O
	2	200	200NHG02B	1015	3	3	O
		224	224NHG02B	1015	3	3	O
		250	250NHG02B	1040	3	3	O
		315	315NHG2B	1235	3	3	N
	03	355	355NHG2B	1255	3	3	O
		400	400NHG2B	1270	3	3	N
		250	250NHG03B	1660	3	3	O
		315	315NHG03B	1690	3	3	O
	3	355	355NHG03B	1715	3	3	O
		400	400NHG03B	1785	3	3	O
		425	425NHG3B	1815	3	3	O
		450	450NHG3B	1815	3	3	O
	800*#	500	500NHG3B	1975	3	3	N
		630	630NHG3B	2095	3	3	N
		800*#	800NHG3B*#	2575	3	3	N

@ Size "0", 6A - 63A on request
Size "1" 80A-160A on request
Insulated grip version available on request
800VAC gG fuse available on request

Size "01", 6A - 80A on request
Rated Voltage 440V
500/ 630/ 800/ 1000/ 1250 Amp | 500 V | Size 4 available on request

* Available in Single Indicator type only

N - Normal; O - On Order

w.e.f from 15th November, 2025

HRC High Speed Fuses - Semi Conductor Protection Fuses - BS88 Type

Rated Voltage 240 V AC/ 150 V DC, Breaking Capacity - 200 kA

240 Vac	Voltage (V)	Rating (Amps)	Catalogue No. / Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class
	240	6	6LCT	240	20	20	N
	240	10	10LCT	240	20	20	N
	240	12	12LCT	240	20	20	O
	240	16	16LCT	240	20	20	N
	240	20	20LCT	240	20	20	N
	240	25	25LET	430	10	10	N
	240	32	32LET	455	10	10	N
	240	35	35LET	455	10	10	O
	240	50	50LET	475	10	10	N
	240	63	63LET	475	10	10	N
	240	80	80LET	500	10	10	N
	240	100	100LET	500	10	10	O
	240	125	125LET	530	10	10	N
	240	160	160LET	550	10	10	N
	240	180	180LET	585	10	10	N
	240	160	160LMT	875	1	1	N
	240	200	200LMT	925	1	1	N
	240	250	250LMT	1130	1	1	N
	240	315	315LMT	1595	1	1	N
	240	355	355LMT	1695	1	1	N
	240	400	400LMT	1795	1	1	N
	240	450	450LMT	2055	1	1	N
	240	400	400LMMT	2385	1	1	O
	240	500	500LMMT	2590	1	1	O
	240	630	630LMMT	2845	1	1	O
	240	710	710LMMT	3010	1	1	O
	240	800	800LMMT	3580	1	1	O
	240	900	900LMMT	4000	1	1	O

N - Normal; O - On Order

Rated Voltage 690 Volts AC/ 500VDC, Breaking Capacity - 200 kA

690 Vac	Voltage (V)	Rating (Amps)	Catalogue No. / Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class
	690	6	6CT	245	20	20	N
	690	10	10 CT	245	20	20	N
	690	12	12 CT	245	20	20	O
	690	16	16 CT	265	20	20	N
	690	20	20 CT	265	20	20	N
	690	15	15 ET	525	10	10	N
	690	25	25 ET	525	10	10	N
	690	32	32 ET	525	10	10	N
	690	35	35 ET	525	10	10	N
	690	40	40 ET	525	10	10	N
	690	45	45 ET	525	10	10	N
	690	56	56 ET	585	10	10	N
	690	63	63 ET	585	10	10	N
	690	80	80 ET	590	10	10	N

N - Normal; O - On Order

w.e.f from 15th November, 2025

HRC High Speed Fuses - Semi Conductor Protection Fuses - BS88 Type

Rated Voltage 690 Volts AC / 500 Volts DC, Breaking Capacity - 200 kA

690 Vac	Voltage (V)	Rating (Amps)	Catalogue No. / Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class
	690	35	35FE	560	10	10	N
	690	40	40FE	560	10	10	O
	690	45	45FE	560	10	10	N
	690	50	50FE	560	10	10	N
	690	63	63FE	630	10	10	N
	690	71	71FE	650	10	10	O
	690	80	80FE	695	10	10	N
	690	90	90FE	825	10	10	N
	690	100	100FE	825	10	10	N
	690	75	75EET	1255	5	5	O
	690	90	90EET	1255	5	5	N
	690	110	110EET	1255	5	5	N
	690	140	140EET	1255	5	5	N
	690	160	160EET	1280	5	5	N
	690	100	100FEE	1310	5	5	N
	690	120	120FEE	1370	5	5	N
	690	140	140FEE	1420	5	5	N
	690	160	160FEE	1440	5	5	N
	690	180	180FEE	1475	5	5	O
	690	200	200FEE	1515	5	5	N
	690	160	160MT	1120	1	1	N
	690	180	180MT	1165	1	1	N
	690	200	200MT	1470	1	1	N
	690	250	250MT	1495	1	1	N
	690	280	280MT	1610	1	1	N
	690	315	315MT	2105	1	1	N
	690	355	355MT	2145	1	1	N
	690	180	180MMT	2085	1	1	N
	690	200	200MMT	2185	1	1	N
	690	225	225MMT	2255	1	1	N
	690	280	280MMT	2315	1	1	N
	690	315	315MMT	2310	1	1	N
	690	355	355MMT	2670	1	1	N
	690	400	400MMT	2770	1	1	N
	690	450	450MMT	2985	1	1	N
	690	500	500MMT	3310	1	1	N
	690	560	560MMT	3630	1	1	N
	690	630	630MMT	3765	1	1	N
	690	180	180FM	1165	1	1	O
	690	200	200FM	1320	1	1	N
	690	225	225FM	1375	1	1	N
	690	250	250FM	1395	1	1	N
	690	280	280FM	1565	1	1	O
	690	315	315FM	2140	1	1	N
	690	350	350FM	2220	1	1	N
	690	400	400FMM	2380	1	1	N
	690	450	450FMM	2485	1	1	N
	690	500	500FMM	2805	1	1	N
	690	550	550FMM	2985	1	1	N
	690	630	630FMM	3495	1	1	N
	690	700	700FMM	3850	1	1	N

N - Normal; O - On Order

w.e.f from 15th November, 2025

Accessories

	Catalogue No. / Type	Trip Indicator accessory pack (each consists of 1 pair of clip & appropriate size Trip Indicator Fuse Link)	MRP (₹)	Pack Quantity	Delivery Class
	EC-250	For use with LET	1085	1 set	O
	EC-600	For use with ET, EET, FE & FEE	1165	1 set	O
	MC-250	For use with LMT & LMMT	1085	1 set	O
	MC-600	For use with FM & FMM	1165	1 set	O
	MC-700	For use with MT & MMT	1220	1 set	O

	Catalogue No. / Type	Micro - Switch	MRP (₹)	Pack Quantity	Delivery Class
	MAI	Micro-switch & Adapter assly.	1415	1	O
	MBI	Micro-switch & Adapter assly.	#	1	O

- Price Available on request

	Catalogue No. / Type	Fuse Clips for Fitting Trip Indicator	MRP (₹)	Pack Quantity	Delivery Class
	ECLIP	For use with LET, ET, EET, FE & FEE	185	10	O
	MCLIP	For use with LMT, LMMT, MT, MMT, FM & FMM	405	10	O
	CL1	Back connected Clip for use with Trip Indicator fuse	1360	1 set	O

	Catalogue No. / Type	Trip Indicators for Fuse Links	MRP (₹)	Pack Quantity	Delivery Class
	TI250-BT	For use with LET, LMT & LMMT	1065	10	O
	TI500-BT	For use with ET, EET, FE & FEE, FM & FMM	1090	1	O
	TI600-BT	For use with ET, EET, FE & FEE, FM & FMM	1360	1	O
	TI700-BT	For use with MT & MMT	1360	1	O
	TI1100-BT	For replacement only	1515	1	O
	TI1500-BT	For replacement only	1565	1	O
	TI2000-BT	For replacement only	1730	1	O

- Price Available on request
N - Normal; O - On Order

NH Fuse base

	Catalogue No. / Type	Fuse Accessories	MRP (₹)	Pack Quantity	Delivery Class
	SD1-S	NH Fuse base 250A, 690VAC DIN Size 1 (Screw Mounting)	1090	3	O
	SD2-S	NH Fuse base 400A, 690VAC DIN Size 2 (Screw Mounting)	1610	3	O
	SD3-S	NH Fuse base 630A, 690VAC DIN Size 3 (Screw Mounting)	2335	3	O
	SD4-S	NH Fuse base 1250A, 690VAC DIN Size 4 (Screw Mounting)	5600	1	O

N - Normal; O - On Order

w.e.f from 15th November, 2025

British Standard Type Range of Fuses for use in Air

	Application (used in)	Voltage (Kv)	Breaking Capacity (kA)	Ratings (Amps)	Catalogue No. / Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class
	Air (Bus Duct / Distribution)	3.3 / 3.6	25	15	3.6ADGHC15	4415	1	1	O
		3.3 / 3.6	25	20	3.6ADGHC20	4415	1	1	O
		3.3 / 3.6	25	25	3.6ADGHC25	4415	1	1	O
		3.3 / 3.6	25	30	3.6ADGHC30	4415	1	1	O
		3.3 / 3.6	25	40	3.6ADGHC40	4415	1	1	O
		3.3 / 3.6	25	45	3.6ADGHC45	4415	1	1	O
		3.3 / 3.6	25	50	3.6ADGHC50	4415	1	1	O
		3.3 / 3.6	25	60	3.6ADGHC60	4415	1	1	O
		3.3 / 3.6	25	70	3.6ADGHC70	4415	1	1	O
		3.3 / 3.6	25	75	3.6ADGHC75	4890	1	1	O
		3.3 / 3.6	25	80	3.6ADGHC80	4890	1	1	O
	Air (Bus Duct / Distribution)	3.3 / 3.6	25	90	3.6ADGHC90	4985	1	1	O
		3.3 / 3.6	25	100	3.6ADGHC100	4985	1	1	O
		6.6 / 7.2	40	10	7.2BDGHC10	4465	1	1	O
		6.6 / 7.2	40	16	7.2BDGHC16	4465	1	1	O
		6.6 / 7.2	40	20	7.2BDGHC20	4465	1	1	O
		6.6 / 7.2	40	25	7.2BDGHC25	4465	1	1	O
		6.6 / 7.2	40	31.5	7.2BDGHC31.5	4465	1	1	O
		6.6 / 7.2	40	35.5	7.2BDGHC35.5	4465	1	1	O
		6.6 / 7.2	40	40	7.2BDGHC40	4465	1	1	O
		6.6 / 7.2	40	45	7.2BDGHC45	4545	1	1	O
		6.6 / 7.2	40	50	7.2BDGHC50	4545	1	1	O
	Air (Bus Duct / Distribution)	6.6 / 7.2	40	56	7.2BDGHC56	4545	1	1	O
		6.6 / 7.2	40	60	7.2BDGHC60	4545	1	1	O
		6.6 / 7.2	40	63	7.2BDGHC63	4840	1	1	O
		6.6 / 7.2	40	71	7.2BDGHC71	4870	1	1	O
		6.6 / 7.2	40	80	7.2BDGHC80	4870	1	1	O
		6.6 / 7.2	40	50	7.2AHGHC50	5560	1	1	O
		6.6 / 7.2	40	60	7.2AHGHC60	5560	1	1	O
		6.6 / 7.2	40	75	7.2AHGHC75	5860	1	1	O
		6.6 / 7.2	40	90	7.2AHGHC90	6190	1	1	O
		6.6 / 7.2	40	100	7.2AHGHC100	6220	1	1	O
		6.6 / 7.2	40	112	7.2AHGHC112	7500	1	1	O
		6.6 / 7.2	40	125	7.2AHGHC125	7500	1	1	O
		6.6 / 7.2	40	140	7.2AHGHC140	8180	1	1	O
		6.6 / 7.2	40	150	7.2AHGHC150	8180	1	1	O
		6.6 / 7.2	40	160	7.2AHGHC160	8415	1	1	N
		6.6 / 7.2	40	160	7.2AHGNB160 (NS)	7835	1	1	O
		6.6 / 7.2	40	50	7.2AHGHB50	5380	1	1	O
		6.6 / 7.2	40	60	7.2AHGHB60	5380	1	1	O
		6.6 / 7.2	40	65	7.2AHGHB65	5665	1	1	O
		6.6 / 7.2	40	75	7.2AHGHB75	5730	1	1	O
		6.6 / 7.2	40	90	7.2AHGHB90	5995	1	1	N
		6.6 / 7.2	40	100	7.2AHGHB100	6020	1	1	O
		6.6 / 7.2	40	112	7.2AHGHB112	6995	1	1	O
		6.6 / 7.2	40	120	7.2AHGHB120	7275	1	1	O
		6.6 / 7.2	40	125	7.2AHGHB125	7275	1	1	O
		6.6 / 7.2	40	140	7.2AHGHB140	7945	1	1	O
6.6 / 7.2	40	150	7.2AHGHB150	7945	1	1	O		
		6.6 / 7.2	40	160	7.2AHGHB160	7945	1	1	O
		6.6 / 7.2	20	30	7.2AEFMO 30	5595	1	1	O
		6.6 / 7.2	20	35	7.2AEFMO 35	5595	1	1	O
		6.6 / 7.2	20	40	7.2AEFMO 40	5595	1	1	O
		6.6 / 7.2	20	50	7.2AEFMO 50	5655	1	1	O
		6.6 / 7.2	20	56	7.2AEFMO 56	5655	1	1	O
		6.6 / 7.2	20	63	7.2AEFMO 63	5655	1	1	O
		6.6 / 7.2	20	71	7.2AEFMO 71	5680	1	1	O
		6.6 / 7.2	20	80	7.2AEFMO 80	5680	1	1	O
		6.6 / 7.2	20	90	7.2AEFMO 90	5800	1	1	O

(#) Available on request
(NS) Non striker

N - Normal; O - On Order

For ordering HV Air Fuse with Single Slot

- 1 - For BD _____ series, add "S" at the end of the cat. number. For ex : For ordering 100A, 7.2BFGHD catalogue no. will be "7.2BFGHD100S"
- 2 - For AH _____ series, replace "C" at end with "B" For ex : For ordering 100A, 7.2AHGH series, catalogue no. will be "7.2AHGHB100"
- 3 - For "7.2BFGHD" ___ series, completely replaced with "7.2AHGHB".

w.e.f from 15th November, 2025

British Standard Type Range of Fuses for use in Air

	Application (used in)	Voltage (Kv)	Breaking Capacity (kA)	Ratings (Amps)	Catalogue No. / Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class
	Air (Bus Duct/ Distribution)	11 / 12	40	6.3	12BDGHC6.3	5255	1	1	O
		11 / 12	40	10	12BDGHC10	5255	1	1	O
		11 / 12	40	16	12BDGHC16	5255	1	1	O
		11 / 12	40	20	12BDGHC20	4980	1	1	O
		11 / 12	40	25	12BDGHC25	4805	1	1	N
		11 / 12	40	31.5	12BDGHC31.5	4840	1	1	O
		11 / 12	40	35.5	12BDGHC35.5	4840	1	1	O
		11 / 12	40	40	12BDGHC40	4870	1	1	O
		11 / 12	40	45	12BDGHC45	4870	1	1	O
		11 / 12	40	50	12BDGHC50	4910	1	1	O
		11 / 12	40	56	12AHGHC56	5620	1	1	O
		11 / 12	40	63	12AHGHC63	5620	1	1	N
		11 / 12	40	70	12AHGHC70	5690	1	1	O
		11 / 12	40	80	12AHGHC80	6160	1	1	N
		11 / 12	40	90	12AHGHC90	6115	1	1	O
		11 / 12	40	100	12AHGHC100	6160	1	1	O
		11 / 12	40	56	12AHGHB56	5650	1	1	O
		11 / 12	40	63	12AHGHB63	5695	1	1	N
		11 / 12	40	65	12AHGHB65	5930	1	1	O
		11 / 12	40	70	12AHGHB70	5930	1	1	N
		11 / 12	40	80	12AHGHB80	6205	1	1	O
		11 / 12	40	90	12AHGHB90	6330	1	1	O
		11 / 12	40	100	12AHGHB100	6330	1	1	N
		11 / 12	40	112	12AKGHD 112	14360	3	3	O
		11 / 12	40	125	12AKGHD 125	14460	1	1	O
		11 / 12	20	3.7	12AEFMO 3.7	5640	1	1	O
		11 / 12	20	12	12AEFMO 12	5580	1	1	O
		11 / 12	20	15	12AEFMO 15	5580	1	1	O
		11 / 12	20	16.8	12AEFMO 16.8	5580	1	1	O
		11 / 12	20	22	12AEFMO 22	5615	1	1	O
		11 / 12	20	26.6	12AEFMO 26.6	5615	1	1	O
		11 / 12	20	30	12AEFMO 30	5615	1	1	O
		11/12	20	33.75	12AEFMO 33.75	5615	1	1	O
		11 / 12	20	37.5	12AEFMO 37.5	5615	1	1	O
		11 / 12	20	42	12AEFMO 42	5670	1	1	O
		11 / 12	20	47.25	12AEFMO 47.25	5670	1	1	O

(#) Available on request

N - Normal; O - On Order

For ordering HV Air Fuse with Single Slot -

1 - For "12BFGHD"___ series, completely replaced with "12AHGHB".

For use in Oil

	Application (used in)	Voltage (Kv)	Breaking Capacity (kA)	Ratings (Amps)	Catalogue No. / Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class
	Oil	6.6 / 7.2	45	100	7.2OEFMA100	5150	1	1	O
	Oil	11 / 12	40	6.3	12OEFMA6.3	6135	3	3	O
		11 / 12	40	10	12OEFMA10	6135	3	3	O
		11 / 12	40	16	12OEFMA16	6135	3	3	O
		11 / 12	40	20	12OEFMA20	6150	3	3	O
		11 / 12	40	25	12OEFMA25	6150	3	3	O
		11 / 12	40	31.5	12OEFMA31.5	6150	3	3	O
		11 / 12	40	40	12OEFMA40	6165	3	3	O
		11 / 12	40	50	12OEFMA50	6165	3	3	O
		11 / 12	40	63	12OEFMA63	6165	3	3	O
11 / 12		40	71	12OHFMA71	6375	3	3	O	
11 / 12		40	80	12OHFMA80	6375	3	3	O	
		11 / 12	40	16	12OHGMA16	7530	3	3	O
		11 / 12	40	25	12OHGMA25	7530	3	3	O
		11 / 12	40	31.5	12OHGMA31.5	7530	3	3	O
		11 / 12	40	40	12OHGMA40	7570	3	3	O
		11 / 12	40	50	12OHGMA50	7570	3	3	O
		11 / 12	40	63	12OHGMA63	7570	3	3	O
		11 / 12	40	80	12OHGMA80	7570	3	3	O
		11 / 12	40	90	12OHGMA90	7855	3	3	O
		11 / 12	40	100	12OHGMA100	8585	3	3	O
		11 / 12	40	125	12OLGMA125	9650	3	3	O

N - Normal; O - On Order

For use in PT / VT & Auxiliary Transformer

	Application (used in)	Voltage (Kv)	Breaking Capacity (kA)	Ratings (Amps)	Catalogue No. / Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class
	VT / PT	3.3 / 3.6	50	3.15	3.6ABWNA3.15	1110	1	1	N
		3.3 / 3.6	50	6.3	3.6ABWNA6.3	1110	1	1	O
		6.6 / 7.2	45	3.15	7.2ABCNA3.15	1215	1	1	N
		6.6 / 7.2	45	6.3	7.2ABCNA6.3	1223	1	1	O
		6.6 / 7.2	45	3.15	7.2ABWNA3.15	1200	1	1	O
		6.6 / 7.2	45	6.3	7.2ABWNA6.3	1200	1	1	O
		11 / 12	45	3.15	12ABCNA3.15	1225	1	1	N
		22 / 24	25	3.15	24ABGNA3.15	2810	1	1	N
	VT / PT	3.3 / 3.6	50	3.15	3.6ABWNS3.15	1205	1	1	O
		6.6 / 7.2	45	3.15	7.2ABCNS3.15	1330	1	1	O
		11 / 12	45	3.15	12ABCNS3.15	1425	1	1	O
	VT / PT	3.3 / 3.6	50	3.15	3.6ABWNT3.15	1360	1	1	O
		6.6 / 7.2	45	3.15	7.2ABCNT3.15	1255	1	1	O
		11 / 12	45	3.15	12ABCNT3.15	1451	1	1	O

N - Normal; O - On Order
1A PT fuse available on request

w.e.f from 15th November, 2025


British Standard Type Range of Fuses for use in Motor Circuits

	Application (used in)	Voltage (Kv)	Breaking Capacity (kA)	Ratings (Amps)	Catalogue No. / Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class
	For use in MV Motor Circuits	3.6	50	5	3.6WDOHS5	4900	1	1	O
		3.6	50	16	3.6WDOHS16	4900	1	1	O
		3.6	50	20	3.6WDOHS20	4900	1	1	N
		3.6	50	25	3.6WDOHS25	4900	1	1	O
		3.6	50	32	3.6WDOHS32	4900	1	1	N
		3.6	50	40	3.6WDOHS40	4900	1	1	O
		3.6	50	50	3.6WDOHS50	4945	1	1	O
		3.6	50	63	3.6WDOHS63	4945	1	1	N
		3.6	50	80	3.6WDOHS80	4945	1	1	O
		3.6	50	50	3.6WDFMO50	7000	1	1	O
		3.6	50	63	3.6WDFMO63	7201	1	1	O
		3.6	50	80	3.6WDFMO80	7155	1	1	O
		3.6	50	100	3.6WDFMO100	7155	1	1	O
		3.6	50	100	3.6WFFMO100	8970	1	1	O
		3.6	50	140	3.6WFFMO140	10000	1	1	O
		3.6	50	160	3.6WFFMO160	10280	1	1	O
		3.6	50	200	3.6WFFMO200	11140	1	1	N
		3.6	50	250	3.6WFFMO250	12625	1	1	O
		3.6	50	315	3.6WFFMO315	14585	1	1	O
		3.6	50	350	3.6WFFMO350	16140	1	1	O
		3.6	50	450	3.6WFFMO450	24270	1	1	O
		3.6	50	630	3.6WKQMO630	31110	1	1	O
	For use in MV Motor Circuits	7.2	45	50	7.2WFNMO50	9985	1	1	O
		7.2	45	63	7.2WFNMO63	9985	1	1	O
		7.2	45	80	7.2WFNMO80	11795	1	1	O
		7.2	45	100	7.2WFNMO100	11795	1	1	O
		7.2	45	125	7.2WFNMO125	13635	1	1	O
		7.2	45	160	7.2WFNMO160	13765	1	1	O
		7.2	45	200	7.2WFNMO200	15755	1	1	O
		7.2	45	250	7.2WFNMO250	18630	1	1	O
		7.2	45	50	7.2WFQMO50	10880	1	1	N
		7.2	45	63	7.2WFQMO63	10985	1	1	N
		7.2	45	80	7.2WFQMO80	12165	1	1	N
		7.2	45	100	7.2WFQMO100	12915	1	1	N
		7.2	45	125	7.2WFQMO125	15065	1	1	N
		7.2	45	160	7.2WFQMO160	15200	1	1	O
		7.2	45	200	7.2WFQMO200	17145	1	1	O
		7.2	45	250	7.2WFQMO250	21240	1	1	O
		7.2	45	350	7.2WKQMO350	28685	1	1	O
		7.2	45	400	7.2WKQMO400	48330	1	1	O

N - Normal; O - On Order

BS Fuse link Type SS/NS/ES


Clip-on Fuse links with Staggered Tags-415 V AC

415 Vac	BS Size	Tag Type	Rated Voltage (Volts)	Rating (Amps)	Cat. No./ Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class	
	E1	SMALL CLIP ON	415	2	SS2	92	20	20	O	SSD
		TAG	415	4	SS4	92	20	20	N	
			415	6	SS6	92	20	20	N	
			415	10	SS10	97	20	20	O	
			415	16	SS16	97	20	20	O	
			415	20	SS20	97	20	20	O	
	F1	CLIP ON	415	2	NS2	135	20	20	N	NSD
		TAG	415	4	NS4	135	20	20	N	
			415	6	NS6	135	20	20	N	
			415	10	NS10	135	20	20	N	
			415	16	NS16	135	20	20	N	
			415	20	NS20	160	20	20	N	
			415	25	NS25	160	20	20	N	
			415	32	NS32	160	20	20	N	
	F2	LONG CLIP ON	415	2	ES2	130	20	20	O	ESD
		TAG	415	4	ES4	130	20	20	O	
			415	6	ES6	130	20	20	O	
			415	10	ES10	130	20	20	O	
			415	16	ES16	130	20	20	O	
			415	20	ES20	130	20	20	O	
			415	25	ES25	135	20	20	O	
			415	32	ES32	135	20	20	O	
			415	36	ES36	135	20	20	O	
			415	50	ES50	185	20	20	N	
			415	63	ES63	190	20	20	N	

N - Normal; O - On Order

BS Fuse link Type EIT

Fuse link with Offset Tags



415 Vac	BS Size	Tag Type	Rated Voltage (Volts)	Rating (Amps)	Cat. No./ Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class	
		OFFSET TAG	415	2	EIT2	150	20	20	O	EITD
		OPEN SLOT	415	4	EIT4	150	20	20	O	
			415	6	EIT6	150	20	20	N	
			415	10	EIT10	150	20	20	N	
			415	16	EIT16	150	20	20	N	
			415	20	EIT20	155	20	20	N	
			415	25	EIT25	155	20	20	N	
			415	32	EIT32	155	20	20	N	
			415	36	EIT36	185	20	20	O	
			415	50	EIT50	185	20	20	O	
			415	63	EIT63	190	20	20	N	

Note: Please discuss with Eaton sales team before placing any orders for these set of products.

N - Normal; O - On Order

w.e.f from 15th November, 2025


Fuse link with Offset Tags Closed Slot

415 Vac	BS Size	Tag Type	Rated Voltage (Volts)	Rating (Amps)	Cat. No./ Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class	
	A2	OFFSET TAG	415	6	TSA6	160	20	20	O	AAO
		CLOSED SLOT	415	10	TSA10	160	20	20	O	
			415	16	TSA16	160	20	20	N	
			415	20	TSA20	160	20	20	O	
			415	25	TSA25	160	20	20	N	
			415	32	TSA32	160	20	20	N	
	A3	OFFSET TAG	415	36	TSS36	190	20	20	N	BAO
		CLOSED SLOT	415	50	TSS50	335	20	20	N	
			415	63	TSS63	335	20	20	N	
	-	OFFSET TAG	415	80	TSDS80	475	10	10	N	OSD
		CLOSED SLOT	415	100	TSDS100	475	10	10	N	
			415	125	TSDS125	475	10	10	N	
	A4		415	125	TSD125	780	10	10	N	CEO
	-	OFFSET TAG	415	125	TSFP125	780	10	10	O	DEO
		CLOSED SLOT	415	160	TSFP160	780	10	10	N	
			415	200	TSFP200	780	10	10	O	

N - Normal; O - On Order

Type - TSDC \ TSK \ TSMS \ TSTS \ TSLS


Fuse Links with Centre Tag Single Slot

415 Vac	BS Size	Tag Type	Rated Voltage (Volts)	Rating (Amps)	Cat. No./ Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class	
	B3	Centre Tag	415	250	TSK250	1465	10	10	N	ED
		Single Slot	415	315	TSK315	1465	10	10	N	
	-	Centre Tag	415	450	TSTS450	2400	1	1	O	SN11(S)
		Single Slot	415	500	TSTS500	2450	1	1	O	SP11(S)
	-	Centre Tag	415	560	TSLS560	3870	1	1	O	
		Single Slot	415	630	TSLS630	3870	1	1	O	SR11(S)
			415	710	TSLS710	3605	1	1	O	
			415	750	TSLS750	3625	1	1	O	
			415	800	TSLS800	5625	1	1	N	

Note: Please discuss with Eaton sales team before placing any orders for these set of products.

N - Normal; O - On Order


Fuse link with Offset Tags Double Slot

415 Vac	BS Size	Tag Type	Rated Voltage (Volts)	Rating (Amps)	Cat. No./ Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class	
	C1	Centre Tag	415	355	TSM355	2565	1	1	O	EF
		Double Slot	415	400	TSM400	2580	1	1	O	
	C2	Centre Tag	415	450	TST450	2120	1	1	O	FF
		Double Slot	415	500	TST500	3870	1	1	O	
	C3	Centre Tag	415	560	TSL560	3870	1	1	O	SR11
		Double Slot	415	630	TSL630	3990	1	1	N	
			415	710	TSL710	3990	1	1	O	
			415	750	TSL750	3995	1	1	O	
			415	800	TSL800	4230	1	1	N	

N - Normal; O - On Order

Type - TM \ TTM \ TLM


Fuse Links with Centre Tags Double Slot

660 Vac	BS Size	Tag Type	Rated Voltage (Volts)	Rating (Amps)	Cat. No./ Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class	
	C1	Centre Tag	660	355	TM355	2415	1	1	O	SP11
		Double Slot	660	400	TM400	2500	1	1	O	
	C2	Centre Tag	660	450	TTM450	2815	1	1	O	R11
		Double Slot	660	500	TTM500	2930	1	1	O	
			660	560	TTM560	3285	1	1	O	
			660	630	TTM630	3425	1	1	O	
	C3	Centre Tag	660	630	TLM630	6140	1	1	O	GF
		Double Slot	660	710	TLM710	6100	1	1	O	
			660	750 & 800	TLM750 & 800	6100	1	1	O	

N - Normal; O - On Order

Type TIA \ TIS \ TCP \ TFP


Fuse with Offset Tags (2 hole fixing - Bolted)

660 Vac	BS Size	Tag Type	Rated Voltage (Volts)	Rating (Amps)	Cat. No./ Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class	
	A2	OFFSET TAG	660	2	TIA2	160	10	10	O	HO7
		CLOSED SLOT	660	4	TIA4	160	10	10	O	
			660	6	TIA6	195	10	10	N	
			660	10	TIA10	195	10	10	N	
			660	16	TIA16	195	10	10	N	
			660	20	TIA20	195	10	10	N	
			660	25	TIA25	195	10	10	N	
			660	32	TIA32	195	10	10	N	
	A3	OFFSET TAG	660	36	TIS36	255	10	10	N	KO7
		CLOSED SLOT	660	40	TIS40	335	10	10	O	
			660	50	TIS50	280	10	10	N	
			660	63	TIS63	280	10	10	N	
	A4	OFFSET TAG	660	80	TCP80	785	6	6	N	L14
		CLOSED SLOT	660	100	TCP100	785	6	6	N	
			660	125	TFP125	1240	3	3	O	M14
			660	160	TFP160	1240	3	3	O	
			660	200	TFP200	1240	3	3	O	

Note: Please discuss with Eaton sales team before placing any orders for these set of products.

w.e.f from 15th November, 2025

Fuse with Central Tags

660 Vac	BS Size	Tag Type	Rated Voltage (Volts)	Rating (Amps)	Cat. No./ Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class	
	B1	CENTRE TAG	660	80	TC80	835	6	6	O	LO9
		SINGLE SLOT	660	100	TC100	835	6	6	N	
			660	80	102TC80	525	6	6	O	
			660	100	102TC100	585	6	6	O	
	B3	CENTRE TAG	660	250	TKF250	1865	1	1	N	NO9
		SINGLE SLOT	660	315	TKF315	1865	1	1	N	

N - Normal; O - On Order

Moulded Fuse Holder and Fuse Base for 415V AC Circuit

Type - SC (Safe Clip)

IS / BS Size Reference	Description	Connection Type	Suitable for Fuse Type	Rating (Amps)	Cat. No. / Type	Rated Voltage (Volts)	MRP (₹)	Pack Qty.	MOQ	Delivery Class
E1	-	Front	SS	20	SC20H	415	295	10	10	O
F1	-	Front	NS	32	SC32H	415	-	10	10	O

N - Normal; O - On Order

Fuse Fittings for LV BS Type of Fuses

Type - NS & SM: Moulded Fuse Holder

IS / BS Size Reference	Description	Connection Type	Suitable for Fuse Type	Rating (Amps)	Cat. No. / Type	Rated Voltage (Volts)	MRP (₹)	Carton Qty.	MOQ	Delivery Class
F1		Front	NS (upto 32A)	32	NSH32	415	320	10	10	N
		Back	NS (upto 32A)	32	NSP32	415	305	10	10	N
		Busbar	NS (upto 32A)	32	NSB32	415	264	10	10	N
A2	Offset Bolted	Front	TIA / TSA	32	SM32H	660	470	10	10	N
		Busbar	TIA / TSA	32	SM32B	660	600	10	10	N
A3	Offset Bolted	Front	TIA / TSS	63	SM63H	660	615	10	10	N
		Busbar	TIA / TSS	63	SM63B	660	690	10	10	N
A4	Offset Bolted	Front	TCP / TSD	125	SM125H	660	1555	5	10	N
		Busbar	TCP / TSD	125	SM125B	660	1710	5	10	N

Note: Please discuss with Eaton sales team before placing any orders for these set of products.

N - Normal; O - On Order

Type GSMJ/GSMK/SMK Ultra-fast Acting Multi Body Fuselink for

Fuselink for Diode & Thyristor Protection

800 \ 1000 Vac	Rated Voltage (Volts)	Rating (Amps)	Cat. No./ Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class
	800	63	GSMJ63	1245	3	3	O
	800	120	GSMJ120	2895	1	1	O
	800	180	GSMJ180	4375	2	2	O
	800	240	GSMJ240	5665	1	1	O
	800	300	GSMJ300	6530	1	1	O
	800	350	GSMJ350	8530	1	1	O
	800	400	GSMJ400	10010	1	1	O
	800	460	GSMJ460	11070	1	1	O
	800	520	GSMJ520	12175	1	1	O
	800	580	GSMJ580	14685	1	1	O
	800	630	GSMJ630	16320	1	1	O
	800	680	GSMJ680	18040	1	1	O
	800	800	GSMJ800	23391	1	1	O
	800	1000	GSMJ1000	29065	1	1	O
	800	1200	GSMJ1200	33135	1	1	O
	1000	63	GSMK63	630	3	3	O
	1000	120	GSMK120	3040	2	2	O
	1000	180	GSMK180	4450	2	2	O
	1000	240	GSMK240	6365	1	1	O
	1000	300	GSMK300	7345	2	2	O
	1000	350	GSMK350	9030	2	2	O
	1000	400	GSMK400	10950	1	1	O
	1000	460	GSMK460	11210	1	1	O
	1000	520	GSMK520	14715	1	1	O
	1000	580	GSMK580	15820	1	1	O
	1000	630	GSMK630	17685	1	1	O
	1000	680	GSMK680	19415	1	1	O
	1000	800	GSMK800	23835	1	1	O
	1000	1000	GSMK1000	-	1	1	O
	1000	1200	GSMK1200	37580	1	1	O
	-	2000	SMK-GSM120-1200	615	1	1	O
	-	400	954GSMJ400	11400	1	1	O
	1000	500	RGS500	9200	1	1	O

N - Normal; O - On Order

Trip Indicator Fuse

	Cat. No. / Type	Rated Voltage (Volts)	MRP (₹)	Pack Qty.	MOQ	Delivery Class
	TI300-BI	300	695	20	20	N
	TI600-BI	600	735	20	20	N
	TI1200-BI	1200	745	20	20	N
	TI2000-BI	2000	840	20	20	N

Note: Please discuss with Eaton sales team before placing any orders for these set of products.

N - Normal; O - On Order

w.e.f from 15th November, 2025

British Standard Type Range of Fuses for use in Motor Circuits

3.6 / 7.2 KV	Rated Voltage (Volts)	Rating (Amps)	Cat. No./ Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class
	3.6	5	K3PGX5	6600	1	1	O
	3.6	10	K3PGX10	6600	1	1	O
	3.6	16	K3PGX16	6600	1	1	O
	3.6	20	K3PGX20	6600	1	1	O
	3.6	25	K3PGX25	6600	1	1	O
	3.6	32	K3PGX32	6600	1	1	O
	3.6	40	K3PGX40	6600	1	1	O
	3.6	50	K3PGX50	6730	1	1	O
	3.6	63	K3PGX63	6745	1	1	O
	3.6	80	K3PGX80	6745	1	1	O
	3.6	100	K81PEX100	11485	1	1	O
	3.6	160	K81PEX160	12885	1	1	N
	3.6	200	K81PEX200	14535	1	1	O
	3.6	250	K81PEX250	16680	1	1	N
	3.6	315	K81PEX315	20165	1	1	O
	3.6	350	K81PEX350	23420	1	1	N
	7.2	50	K81SVX50	14245	1	1	O
	7.2	63	K81SVX63	14380	1	1	N
	7.2	80	K81SVX80	15670	1	1	N
	7.2	100	K81SVX100	18005	1	1	N
	7.2	125	K81SVX125	19790	1	1	N
	7.2	160	K81SVX160	20160	1	1	O
	7.2	200	K81SVX200	23535	1	1	O
	7.2	250	K81SVX250	28905	1	1	O
	7.2	50	KSVX50	15150	1	1	O
	7.2	63	KSVX63	15150	1	1	O
	7.2	80	KSVX80	15360	1	1	O
	7.2	100	KSVX100	14500	1	1	O
	7.2	125	KSVX125	15640	1	1	O
	7.2	160	KSVX160	17700	1	1	O
	7.2	200	KSVX200	20165	1	1	O
	7.2	250	KSVX250	23045	1	1	O

Note: Please discuss with Eaton sales team before placing any orders for these set of products.

N - Normal; O - On Order

Cross Reference Chart

LV BUS FUSES

Clip on Type

BS Size	Bussmann	Bussmann
E1	SSD	SS
F1	NSD	NS
F2	ESD	ES

Bolted Type - 550V Range

BS Size	Bussmann	Bussmann*
A1	NITD	NIT
A2	AAO	TSA
A3	BAO*	TSS
A4	CEO	TSD
-	OSD	TSDS
C2	FF	TST
C3	GF	TLM
-	GG	TLT

*Fuses are 415V rated

Bolted Type - 660V Range

BS Size	Bussmann	Bussmann
A2	HO7-660	NIT
A3	KO7-660	TSA
A4	L14-660	TSS
-	M14-660	TSD
B1	LO9-660	TSDS
B2	MO9-660	TST
B3	NO9-660	TLM
B4	PO9-660	TLT
C1	P11-660	TLM
C2	R11-660	TLT

Bolted Type - 415V Range

BS Size	Bussmann	Bussmann
-	EITD	EIT
-	DEO	TSFP
B1	CD	TSDC
B2	DD	TSF
B3	ED	TSF/TSK
B4	ED	TSK/TSM
-	SN11 (S)	TSMS
-	SP11 (S)	TSTS
-	SR11 (S)	TSLS
C1	EF	TSM
-	SR11	TSL

LV NH DIN FUSES

BS Size	Bussmann	Bussmann	Brand 2	Brand 3
400 / 415 Volts				
SIZECOO/000	NHG000B-400	NA	NA	
SIZE 00	NHG00B-400	NA	NA	HN SIZE00
SIZE 1	NHG01-400 /NHG1-40	NA	NA	HN SIZE1
SIZE 2	NHG02-400 /NHG2-40	NA	NA	HN SIZE2
SIZE 3	NHG03-400 /NHG3-40	NA	NA	HN SIZE3
500 Volts				
SIZECOO/000	NHG000B	VSA	3NA38	NA
SIZE 00	NHG00B	VSF	3NA10	NA
SIZE 1	NHG01 /NHG1	VSK	3NA12	NA
SIZE 2	NHG02 /NHG2	VST	3NA13	NA
SIZE 3	NHG03 /NHG3		3NA14	NA
660 / 690 Volts				
SIZE 00	NHG00B-690	NA	NA	NA
SIZE 1	NH1G-690	NA	NA	NA
SIZE 2	NH2G-690	NA	NA	NA
SIZE 3	NH3G-690	NA	NA	NA

LV NH DIN BASES

Suitable for size	Bussmann		Bussmann	Brand 2	Brand 3
	TYPE	AMPS			
C00/000/00	SD00 - D	160	ISG160	3NH3030 / 3032	HB160
01/1	SD 1 - S	250	ISG250	3NH3230	HB250
02/2	SD 2 - S	400	ISG400	3NH3330	HB800
03/3	SD 3 - S	630	ISG630	3NH3430	HB800

LV BS88 BASES

BS SIZE	Bussmann			Bussmann	Brand 2	Brand 3
	FUSE TYPES	TYPE	AMPS			
Old Type						
F1	NSD/FO6	FA	32	NSH	NA	HD32H
F1	NSD/FO6	FB	32	NSP	NA	HD32P
F1	NSD/FO6	FD	32	NSB	NA	HD32B
A2	HO7 / AAO / FO7	HA	32	SM32H	NA	HK32H
A2	HO7 / AAO / FO7	HD	32	SM32B	NA	HK32B
A3	TO7 / BAO / KO7	KA	63	SM63H	NA	HK63H
A3	TO7 / BAO / KO7	KD	63	SM63B	NA	HK63B
A4	L14 / CEO / DEO@ / M14@ / KL14	LA	125	SM125H	NA	HK125H
A4	L14 / CEO / DEO@ / M14@ / KL14	LD	125	SM125B	NA	HK125B
	M14@ / KL14					
New Safeloc Type						
F1	NSD / FO6	NNSF	32	SC32H	3NW 32	NA
					NNSF	
F2	ESD	ENSF	63	SC63H	NA	NA
New Range - Cam Master						
A2	HO7 / AAO / FO7	CM32F	32		3NW CM32F9	NA
A3	TO7 / BAO / KO7	CM63F	63		3NW CM63F9	NA
	OSD	CM100F	100		3NW CM100F9	NA

@ - Upto 125A only

- The chart is intended for guidance purpose only, considering physical replaceability
- In identical operating condition, Bussmann fuse can be used to achieve similar performance
- Other makes may not necessarily have identical performance. Relevant data like rated voltage, breaking capacity, let thru' current, etc. also need to be evaluated while evaluating fuse performance

HIGHSPEED BS88 FUSES

BS Size		Bussmann		Brand 4	
TYPE	RANGE	TYPE	RANGE	TYPE	RANGE
240 Volts Range					
LCT	6-20	GSA	5-20	2.5URE	6-20
LET	25-180	GSA	25-100	2.5URGS/URZ	25-180
LMT	160-450	GS450	150-200	2.5URGG	150-200
LMT	160-450	GS450	300-500	2.5URGH	300-500
LMMT	400-900	-	-	-	-
690 Volts Range					
CT	6-20	GSB	5-20	6.6URE	6-20
ET	25-80	GSB	25-75	6.6URS	25-75
ET	25-80	GSG1000	16-55	6.6URS	16-55
EET	90-160	GSG1000	75-150	6.6URT	75-140
FM	180-350	GS1000	100-200	6.6URGL/UR	100-250
MT	160-355	GS1000	100-200	6.6URGL/UR	100-250
MMT	180-710	GS1000	300-500	-	-
MMT	180-710	GSG1000	175-350	6.6URGM/URU	175-350

HV FUSES

Appl. used in	Bussmann	Bussmann
Air	ADGHC	H2CAS
Air	ADOH6 / ADOH7	K3PGX
Air	BFGHD	H2CAS
Air	BDGHC	H2CAS
Air	AHGHG	H2CAS
Oil	OHGMA/OLGMA	KEMXO
Oil	OEFMA/OHFMA	KEBXO
VT/PT	ABWNA	VTF
VT/PT	ABCNA	VTF

Appl. used in	Bussmann	Bussmann
VT/PT	ABCNS	5xVTF
Motor Ckt.	WDOHS	K3PGX
Motor Ckt.	WDFMO/ WFFMO	K81PEX/ K81PRX
Motor Ckt.	WKFFMO	K82PEX
Motor Ckt.	WFQMO	K81SVX/ K81SRX
Motor Ckt.	WKQMO	K82SSX

w.e.f from 15th November, 2025



State-of-the-art manufacturing facility, Pondicherry

America | Europe | Middle East | Africa | Asia Pacific

Electrical standards and certifications



PRICE :

- For items marked (#), prices available on request.
- Prices are subject to change without prior notice.
- This Price list supersedes all previous Price Lists.
- Price prevailing at the time of dispatch will only be applicable.
- For prices of any special products not listed here, please contact us
- Prices are Ex-Pondicherry, exclusive of packing, forwarding, freight & insurance.
- Company reserves the right to issue amendments which may arise due to any errors in the Price List

TAXES AND DUTIES :

- All prices in this document are inclusive of GST.
- Order Postponement or cancellation is not allowed.
- For all shipments, orders to be in multiples of the carton quantity.
- All prices are in Rupees (₹) per individual item unless stated otherwise.

This price list is intended to clearly present comprehensive product data and provide technical information that will help the end user with design applications. Eaton reserves the right, without notice, to change design or construction of any products or discontinue or limit distribution of any products. Eaton also reserves the right to change or update, without notice, any technical information contained in this price list. Once a product has been selected, it should be tested by the user in all possible applications. The information contained in this price list is correct at the time of publication, but we reserve the right to supply products differing in construction or performance.

For more information, please reach out to our Eaton sales representative.

w.e.f from 15th November, 2025

[illegible]



Powering Business Worldwide

India Head Office

Eaton Power Quality Pvt. Ltd.
2, EVR Street, Sedarpet
Industrial Estate
Pondicherry - 605111
Tel: +91 413 2672000
Enquiries - eatonelectricalindia@eaton.com

Branch Offices

Mumbai

Eaton Power Quality Pvt. Ltd.
Unit No. 101 & 102 "A" Wing,
1st floor, 215 Atrium, Andheri
- Kurla Road, Andheri (East)
Mumbai - 400093
Mob - 8754278882 / 9833014167

Bangalore

4th Floor, Prestige Atrium, Central
Street, Bangalore, India - 560001
Tel: +91 80 49012200
Mob - 9916514234 / 8754378882

Chennai

No. 334, Futura Tech Park, Block B,
1st floor, Rajiv Gandhi Salai,
Sholinganallur, Chennai - 600119
Mob - 7358110211

Pune

4th & 6th Floor, T-29/31, Om Chambers
Near Sharayu Toyota showroom
MIDC Bhosari.
Pimpri-Chinchwad, Pune
Maharashtra - 411026
Mob: 9320141508

Delhi

Unit A1 & B1, 3rd Floor, TDI Centre,
Plot No. 7, Jasola, New Delhi - 110025
Tel: +91 11 45851800
Mob - 8754268882 / 9811086586

Hyderabad

Mob - 9629960108

Kolkata

Mob - 8925453636

Coimbatore

Mob - 7305078331

Vadodara

Mob - 9879355485

Chandigarh

Mob - 8754348882 / 9501177119

Ahmedabad

Mob - 8754298882

Indore

Mob - 7823901874

Customer Care Center:

Toll free number: 1800 425 5758, 1800 102 4620

Emergency number: 893 922 2522

**Email: eatonelectricalindia@eaton.com
helpdeskelectrical@eaton.com**



Powering Business Worldwide

[Eaton.com/in](https://www.eaton.com/in)